

AMENDMENT TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims

Claims 1-5 (*Canceled*).

6. (*Currently amended*) A device for damping oscillations of a combustion chamber comprising:

at least one resonator structured and arranged to dampen vibrations being connected to a pre-chamber ~~in a vibration-damping manner~~,

wherein the pre-chamber is connected to ~~[[a]] the combustion chamber in a vibration-damping manner~~ to dampen vibrations via at least one passage channel.

7. (*Previously presented*) The device of claim 6, wherein the combustion chamber adjoins an injection head having at least one injection element.

8. (*Previously presented*) The device of claim 7, wherein the injection head conducts a fuel flow into the combustion chamber.

9. (*Previously presented*) The device of claim 8, wherein the pre-chamber is arranged upstream of the at least one injection element.

10. *(Previously presented)* The device of claim 8, wherein the pre-chamber is arranged in an area of the at least one injection element.

11. *(Previously presented)* The device of claim 6, wherein the pre-chamber is in fluid connection with a fuel flow.

12. *(Previously presented)* The device of claim 6, wherein the at least one passage channel is part of an injection element.

13. *(Previously presented)* The device of claim 6, wherein the combustion chamber is part of a rocket engine.

14. *(Previously presented)* A system for damping oscillations, the system comprising:
a combustion chamber;
an injection head arranged upstream of the combustion chamber;
a pre-chamber arranged upstream of the injection head; and
at least one resonator structured and arranged to dampen vibrations of the combustion chamber and comprising one of:

an opening communicating with the pre-chamber; and

an opening communicating with an open area of the injection head.

15. *(Previously presented)* The system of claim 14, wherein the combustion chamber comprises an outlet arranged opposite the injection head.

16. *(Previously presented)* The system of claim 14, wherein the opening communicating with the pre-chamber comprises a circumferential opening.

17. *(Previously presented)* The system of claim 14, wherein the at least one resonator is annular shaped.

18. *(Previously presented)* The system of claim 14, wherein the at least one resonator comprises a sleeve which extends into the open area of the injection head.

19. *(Previously presented)* The system of claim 14, wherein the at least one resonator comprises a sleeve oriented along a direction of gas flow and which extends into the open area of the injection head.

20. *(Previously presented)* The system of claim 14, wherein the at least one resonator comprises a plurality of sleeves at least one of oriented along a direction of gas flow and extending into the open area of the injection head.

21. *(Previously presented)* The system of claim 14, wherein the at least one resonator comprises a radially oriented opening communicating with the pre-chamber.

22. *(Previously presented)* The system of claim 14, wherein the at least one resonator comprises a plurality of radially oriented openings communicating with the pre-chamber.

23. *(Previously presented)* The system of claim 14, wherein the at least one resonator comprises a radially oriented opening communicating with the open area of the injection head.

24. *(Previously presented)* The system of claim 14, wherein the at least one resonator is one of:

integrally formed in a side wall of the pre-chamber;

integrally formed in an end wall of the pre-chamber; and

integrally formed in a side wall of the injection head.

25. *(Previously presented)* A system for damping oscillations of a rocket engine, the system comprising:

a combustion chamber;

an injection head arranged upstream of the combustion chamber;

a pre-chamber arranged upstream of the injection head; and

at least one resonator structured and arranged to dampen vibrations of the combustion chamber and comprising one of:

an opening communicating with the pre-chamber; and

an opening communicating with an open area of the injection head.